

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

©	∅ 0.1	A
---	-------	---



Angles ± 2° Drilled holes +0.25 -0  
 All sharp edges removed R0.2 +0.2  
 Inside and Outside deburred  
 Surface roughness max. Ra 3.2

Stroke	Tol. +1.8 -1.6
--------	-------------------

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	4.13 kg
Item	CFGCY0063842	Reference	0104640	
Description	C2S.30.20.450 OHNE~OHNE			
Finish	Primer			



CFGCY0063842 - C2S.30.20.450 OHNE~OHNE



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 40 x 30 ST52-H10 CB 40-5H10 L=0.531	1
LSN04E	2	Welding-stud 1/4" BSP	2
DS3903001A	3	Reinforced Endcap C2/C3/P2 - Bore 30	1
MDL-090346	4	Rod - Hard Chrome Shaft 20 - HAC20 L=0.553	1
DS2903013020	5	Cylinder-head C2 - Bore 30 - Rod 20 - 250 bar	1
ASU2028653	6	Scraper 20 x 28.6 x 5.3	1
SA202857UN	7	Rod-seal 20 x 28 x 5.7 UN	1
BU2507262	8	Backup-ring 25.86 x 2.18 x 1.14	1
OR250726290P001	9	O-ring 25.07 x 2.62 - 90'-shore	1
OR2982262	10	O-ring 29.82 x 2.62	1
DS2903004	11	Cylinder-piston C2 - Bore 30	1
ZA3021135DBM	12	Piston-seal 30 x 21 x 13.5/2.1	1
MDL-020787	13		1
SLBMM1215	14	Seallock-nut M12x1.5 Ø30mm	1
SP04M	15	Dust plug outer thread 1/4" BSP	2