



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{Ⓢ} \text{ } \phi \text{ } 0.1 \text{ } \text{A}$	Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed $R0.2 +0.2$ Inside and Outside deburred Surface roughness max. $Ra \text{ } 3.2$	Stroke Tol. $+1.8$ -1.6
Up to	6	30	120	400	1000	2500			
Tol.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2			

	Drawn		Pressure	250 bar
	Cust. Ref.	Kandolf Hannes HW	Weight	45.43 kg
Item	CFGCY0077426	Reference	0502064	
Description	C2S.70.40.2080 Boden/Bohrung~OHNE			
Finish	Primer			

CFGCY0077426 - C2S.70.40.2080 Boden/Bohrung~OHNE



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 80 x 70 ST52-H10 CB 80-5H10 L=2.183	1
LSN08E	2	Welding-stud 1/2" BSP	2
MDL-011640	3	Machined Endcap/Circular with Hole 25.2mm - Bore 70	1
MDL-090346	4	Rod - Hard Chrome Shaft 40 - HAC40 L=2.206	1
DS2907013040	5	Cylinder-head C2 - Bore 70 - Rod 40 - 250 bar	1
DS2907004	6	Cylinder-piston C2 - Bore 70	1
DS2906015	7	Swage ring C25 Bore 60/63/70	1
SP08M	8	Dust plug outer thread 1/2" BSP	2