



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{Ⓢ} \text{ } \varnothing \text{ } 0,1 \text{ } \text{ } A$	Angles $\pm 2^\circ$ Drilled holes $+0,25 -0$ All sharp edges removed $R0,2 +0,2$ Inside and Outside deburred Surface roughness max. $Ra \text{ } 3,2$	Stroke Tol. $+1,8$ $-1,6$
Up to	6	30	120	400	1000	2500			
Tol.	$\pm 0,1$	$\pm 0,2$	$\pm 0,3$	$\pm 0,5$	$\pm 0,8$	$\pm 1,2$			

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	5.22 kg
Item	CFGCY0074486	Reference	0328189	
Description	C2S.50.25.200 Gaffel/65x50x25~GEEN			
Finish	Primer			



CFGCY0074486 - C2S.50.25.200 Gaffel/65x50x25~GEEN



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 60 x 50 ST52-H10 CB 60-5H10 L=0.292	1
LSN06E	2	Welding-stud 3/8" BSP	2
DC3905001	3	Endcap C2/C3 - Bore 50	1
FS1714	4	Clevis 65x50x25 hole 25	1
MDL-090346	5	Rod - Hard Chrome Shaft 25 - HAC25 L=0.314	1
DS2905013025	6	Cylinder-head C2 - Bore 50 - Rod 25 - 250 bar	1
ASU2533653	7	Scraper 25 x 33.6 x 5.3	1
SA253368UN	8	Rod-seal 25 x 33 x 6.8 UN	1
BU4404353	9	Backup-ring 44.04 x 3.53 x 1.02	1
OR4445353	10	O-ring 44.45 x 3.53	1
OR4890262	11	O-ring 48.90 x 2.62	1
DS2905004	12	Cylinder-piston C2 - Bore 50	1
ZA5034184DBM	13	Piston-seal 50 x 34 x 18.4/6.3	1
OR219026290P001	14	O-ring 21.90 x 2.62 - 90'-shore	1
DS2905015	15	Swage ring C25 Bore 50	1
SP06M	16	Dust plug outer thread 3/8" BSP	2