

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2


© Ø 0.1 A

Angles ± 2° Drilled holes +0.25 -0
All sharp edges removed R0.2 +0.2
Inside and Outside deburred
Surface roughness max. Ra 3.2

Stroke
Tol. +1.8
-1.6

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	19.92 kg
Item	CFGY0072265	Reference	7774230	
Description	C2S.70.30.980 GF25DO~GK25DO			
Finish	Primer & RAL7012 Basalt-grey High-Gloss			

CFGCY0072265 - C2S.70.30.980 GF25DO~GK25DO



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 80 x 70 ST52-H10 CB 80-5H10 L=1.083	1
LSN06E	2	Welding-stud 3/8" BSP	2
DC3907001	3	Endcap C2/C3 - Bore 70	1
GF25DO	4	Spherical-bearing GF 25 DO	1
MDL-090346	5	Rod - Hard Chrome Shaft 30 - HAC30 L=1.106	1
GK25DO	6	Spherical-bearing GK 25 DO	1
DS2907013030	7	Cylinder-head C2 - Bore 70 - Rod 30 - 250 bar	1
ASU3038653	8	Scraper 30 x 38.6 x 5.3	1
SA30407UN	9	Rod-seal SA 30 x 40 x 7 UN	1
BU5969534	10	Backup-ring 59.69 x 5.34 x 1.52	1
OR5969533P001	11	O-ring 59.69 x 5.33	1
OR6952262	12	O-ring 69.52 x 2.62	1
DS2907004	13	Cylinder-piston C2 - Bore 70	1
ZA7050224DBM	14	Piston-seal 70 x 50 x 22.4/6.3	1
OR250726290P001	15	O-ring 25.07 x 2.62 - 90'-shore	1
DS2906015	16	Swage ring C25 Bore 60/63/70	1
SP06M	17	Dust plug outer thread 3/8" BSP	2