


All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{Ⓢ} \text{ } \phi \text{ } 0.1 \text{ } \text{A}$	Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed $R0.2 +0.2$ Inside and Outside deburred Surface roughness max. Ra 3.2	Stroke
Up to	6	30	120	400	1000	2500			Tol. +1.8
Tol.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2			-1.6

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	24.86 kg
Item	CFGY0079634	Reference	7444449	
Description	C2L.70.40.1000 Douille/50~AUCUN			
Finish	Primer			

CFGCY0079634 - C2L.70.40.1000 Douille/50~AUCUN



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 80 x 70 ST52-H10 CB 80-5H10 L=1.103	1
LSN06E	2	Welding-stud 3/8" BSP	2
DS2907001RO	3	Rota endcap for bore 70	1
LA2400	4	Rota Sensor Stroke 1000mm, 10-30 V input, V + mA output	1
916510B	5	Grub screw M5x10 45H DIN 916	1
VSR02WD	6	End Plug (CS) R1/8 VS-R02-WD	1
	7	Bush 50 x 25 L=70	1
MDL-090346	8	Rod - Hard Chrome Shaft 40 - HAC40 L=1.120	1
DS2907013040	9	Cylinder-head C2 - Bore 70 - Rod 40 - 250 bar	1
DS2907004	10	Cylinder-piston C2 - Bore 70	1
7993RW24	11	Locking-ring RW 24 DIN 7993 for Axle	1
SP06M	12	Dust plug outer thread 3/8" BSP	2