



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\varnothing 0.1$ A Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed R0.2 $+0.2$ Inside and Outside deburred Surface roughness max. Ra 3.2	Stroke
Up to	6	30	120	400	1000	2500		Tol. +1.8
Tol.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2		-1.6

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	1.85 kg
Item	CFGCY0079670	Reference	0609000	
Description	C2S.25.16.200 NONE-NONE			
Finish	Primer			



CFGCY0079670 - C2S.25.16.200 NONE~NONE



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 35 x 25 ST52-H10 CB 35-5H10 L=0.275	1
LSN04E	2	Welding-stud 1/4" BSP	2
DS3902501A	3	Reinforced Endcap C2/C3/P2 - Bore 25	1
MDL-090346	4	Rod - Hard Chrome Shaft 16 - HAC16 L=0.297	1
DS2902513016	5	Cylinder-head C2 - Bore 25 - Rod 16 - 250 bar	1
ASU1624653	6	Scraper 16 x 24.6 x 5.3	1
SA16225UN	7	Rod-seal 16 x 22 x 5 UN	1
BU2064262	8	Backup-ring 20.64 x 2.62 x 1.4	1
OR2063262	9	O-ring 20.63 x 2.62	1
OR2347262	10	O-ring 23.47 x 2.62	1
DS2902504	11	Cylinder-piston C2 - Bore 25	1
ZA2515125DBM	12	Piston-seal 25 x15 x 12.5 DBM	1
MDL-020787	13		1
SLBMM1015	14	Seallock-nut M10x1.5 Ø25mm	1
SP04M	15	Dust plug outer thread 1/4" BSP	2