

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

©	∅ 0.1	A
---	-------	---



Angles ± 2° Drilled holes +0.25 -0
 All sharp edges removed R0.2 +0.2
 Inside and Outside deburred
 Surface roughness max. Ra 3.2

Stroke
 Tol. +1.8
 -1.6

	Drawn		Pressure	250 bar
	Cust. Ref.	MCA-4110-K	Weight	10.38 kg
Item	CFGCY0066412	Reference	0100485	
Description	P2S.30.770 GF20HO2RS~GF20HO2RS			
Finish	Primer & RAL7016 Anthracite-grey High-Gloss			



CFGCY0066412 - P2S.30.770 GF20HO2RS~GF20HO2RS



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 45 x 35 ST52-H10 CB 45-5H10 L=0.802	1
LSN0645	2	Welding-stud 3/8" BSP L=45mm	1
DC3903501	3	Endcap C2/C3/P2 - Bore 35	1
GF20HO2RS	4	Housing for GF-20	2
GE20HO2RS	5	Spherical-plain-bearing GE 20 HO 2RS	2
MDL-090346	6	Rod - Hard Chrome Shaft 30 - HAC30 L=0.853	1
PC2903007	7	Cylinder-head P2 - Rod 30	1
ASU3038653	8	Scraper 30 x 38.6 x 5.3	1
SA30407UN	9	Rod-seal SA 30 x 40 x 7 UN	1
OR4252262	10	O-ring 42.52 x 2.62	1
BU4252262	11	Backup-ring 42.52 x 2.62 x 1.14	1
7993RW30	12	Locking-ring RW 30 DIN 7993 for Axle	1
PC2903003	13	Guide ring PC25 rod 30/35x25x12 PC 2-903003	1
SP06M	14	Dust plug outer thread 3/8" BSP	1
HBV905	15	Hose br val VB-3/8 " BSP HBV 9-05	1