


All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{Ⓢ} \text{ } \varnothing \text{ } 0.1 \text{ } \text{A}$	Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed R0.2 $+0.2$ Inside and Outside deburred Surface roughness max. Ra 3.2	Stroke
Up to	6	30	120	400	1000	2500			Tol. +1.8
Tol.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2			-1.6

	Drawn		Pressure	320 bar
	Cust. Ref.	Rouleau Vors	Weight	51.46 kg
Item	CFGY0076251	Reference	7120183	
Description	C3S.90.50.915 Douille/60~Douille/60			
Finish	Primer & RAL9005 Jet-black Matt			

CFGCY0076251 - C3S.90.50.915 Douille/60~Douille/60



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 110 x 90 ST52-H8 CB 110-10H8 L=1.053	1
LSN06D	2	Welding-stud 3/8" BSP L=35	2
DC3909001	3	Endcap C2/C3 - Bore 90	1
	4	Bush 60 x 34 L=90	1
ZB303430BDA	5	Bearing-bush Permaglide P2 - d=30, D=34, L=30 (low-maintenance)	4
MDL-090346	6	Rod - Hard Chrome Shaft 50 - HAC50 L=1.078	1
	7	Bush 60 x 34 L=60	1
DS3909013050	8	Cylinder-head C3 - Bore 90 - Rod 50 - 320 bar	1
ASU5060653T38	9	Scraper 50 x 60.6 x 5.3 - T38	1
SA506010UN	10	Rod-seal 50 x 60 x 10 UN	1
SAS5065163	11	Rod-seal 50 x 65.1 x 6.3	1
GRI505597	12	Guide-ring 50 x 55 x 9.7	2
BU7874534	13	Backup-ring 78.74 x 5.34 x 1.52	1
OR7874533P001	14	O-ring 78.74 x 5.33	1
OR8857262	15	O-ring 88.57 x 2.62	1
DS3909004	16	Cylinder-piston C3 - Bore 90	1
ZAS9074563	17	Piston-stepseal 90 x 74.5 x 6.3	1
GRE908515	18	Wear-ring 90 x 85 x 15	2
OR408735390P001	19	O-ring 40.87 x 3.53 - 90'-shore	1
916816	20	Grub screw M8x16 45 H zinc-pl.	1
SP06M	21	Dust plug outer thread 3/8" BSP	2
GN81180	22	Grease nipple M8x1 - 180°	2