



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

© Ø 0.1 A

Angles ± 2° Drilled holes +0.25 -0
All sharp edges removed R0.2 +0.2
Inside and Outside deburred
Surface roughness max. Ra 3.2

Stroke
Tol. +1.8
-1.6

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	7.52 kg
Item	CFGCY0079580	Reference	0416967	
Description	C2S.40.25.575 Fond/Circulaire~GK20DO			
Finish	Primer			



CFGCY0079580 - C2S.40.25.575 Fond/Circulaire~GK20DO



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 50 x 40 ST52-H10 CB 50-5H10 L=0.660	1
LSN06E	2	Welding-stud 3/8" BSP	2
MDL-011636	3	Machined Endcap/Circular with Hole 20mm - Bore 40	1
MDL-090346	4	Rod - Hard Chrome Shaft 25 - HAC25 L=0.681	1
GK20DO	5	Spherical-bearing GK 20 DO	1
DS2904013025	6	Cylinder-head C2 - Bore 40 - Rod 25 - 250 bar	1
ASU2533653	7	Scraper 25 x 33.6 x 5.3	1
SA253368UN	8	Rod-seal 25 x 33 x 6.8 UN	1
BU3452353	9	Backup-ring 34.52 x 3.53 x 1.02	1
OR3452353	10	O-ring 34.52 x 3.53	1
OR3934262	11	O-ring 39.34 x 2.62	1
DS2904004	12	Cylinder-piston C2 - Bore 40	1
ZA4024184DBM	13	Piston-seal 40 x 24 x 18.4/6.3	1
OR171326290	14	O-ring 17.13 x 2.62 - 90'-shore	1
DS2904015	15	Swage ring C25 Bore 40	1
SP06M	16	Dust plug outer thread 3/8" BSP	2
GN61180	17	Grease nipple M6 - 180°	2