



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

| | | | | | | | | |
|-------|-----------|-----------|-----------|-----------|-----------|-----------|--|-----------|
| Above | - | 6 | 30 | 120 | 400 | 1000 | All diameters $\varnothing 0.1$ A Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed R0.2 $+0.2$ Inside and Outside deburred Surface roughness max. Ra 3.2 | Stroke |
| Up to | 6 | 30 | 120 | 400 | 1000 | 2500 | | Tol. +1.8 |
| Tol. | ± 0.1 | ± 0.2 | ± 0.3 | ± 0.5 | ± 0.8 | ± 1.2 | | -1.6 |

| | | | | |
|-------------|-------------------------|--|-----------|---------|
| | Drawn | | Pressure | 250 bar |
| | Cust. Ref. | | Weight | 1.85 kg |
| Item | CFGCY0079672 | | Reference | 0328325 |
| Description | C2S.25.16.200 GEEN-GEEN | | | |
| Finish | Primer | | | |



CFGCY0079672 - C2S.25.16.200 GEEN~GEEN



| PARTNO | POS. | DESCRIPTION | QTY. |
|--------------|------|--|------|
| MDL-090348 | 1 | Tube - Cylinder tube 35 x 25 ST52-H10 CB 35-5H10 L=0.275 | 1 |
| LSN04E | 2 | Welding-stud 1/4" BSP | 2 |
| DS3902501A | 3 | Reinforced Endcap C2/C3/P2 - Bore 25 | 1 |
| MDL-090346 | 4 | Rod - Hard Chrome Shaft 16 - HAC16 L=0.297 | 1 |
| DS2902513016 | 5 | Cylinder-head C2 - Bore 25 - Rod 16 - 250 bar | 1 |
| ASU1624653 | 6 | Scraper 16 x 24.6 x 5.3 | 1 |
| SA16225UN | 7 | Rod-seal 16 x 22 x 5 UN | 1 |
| BU2064262 | 8 | Backup-ring 20.64 x 2.62 x 1.4 | 1 |
| OR2063262 | 9 | O-ring 20.63 x 2.62 | 1 |
| OR2347262 | 10 | O-ring 23.47 x 2.62 | 1 |
| DS2902504 | 11 | Cylinder-piston C2 - Bore 25 | 1 |
| ZA2515125DBM | 12 | Piston-seal 25 x15 x 12.5 DBM | 1 |
| MDL-020787 | 13 | | 1 |
| SLBMM1015 | 14 | Seallock-nut M10x1.5 Ø25mm | 1 |
| SP04M | 15 | Dust plug outer thread 1/4" BSP | 2 |