

M30x3.5 - L=60 mm

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

© Ø 0.1 A



Angles ± 2° Drilled holes +0.25 -0
All sharp edges removed R0.2 +0.2
Inside and Outside deburred
Surface roughness max. Ra 3.2

Stroke
Tol. +1.8
-1.6

	Drawn		Pressure	250 bar
	Cust. Ref.	Werdener Straße , Düsseldorf	Weight	45.77 kg
Item	CFGY0076068	Reference	0163375	
Description	P2S.60.1100 GK35DO~M30x3.5			
Finish	Primer & RAL6018 Yellow-green High-Gloss			



CFGCY0076068 - P2S.60.1100 GK35DO~M30x3.5



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 75 x 65 ST52-H10 CB 75-5H10 L=1.145	1
LSN06E	2	Welding-stud 3/8" BSP	1
DC3906501	3	Endcap P2 - Bore 65	1
GK35DO	4	Spherical-bearing GK 35 DO	1
MDL-090346	5	Rod - Hard Chrome Shaft 60 - HAC60 L=1.477	1
PC2906007	6	Cylinder-head P2 - Rod 60	1
ASU6070653	7	Scraper 60 x 70.6 x 5.3	1
SA607010UN	8	Rod-seal 60 x 70 x 10 UN	1
OR7270262	9	O-ring 72.70 x 2.62	1
BU7269262	10	Backup-ring 72.69 x 2.62 x 1.14	1
7993RW60	11	Locking-ring RW 60 DIN 7993 for Axle	1
PC2906003	12	Guide ring PC25 rod 60/65x55x15 PC 2-906003	1
SP06M	13	Dust plug outer thread 3/8" BSP	1