

| All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask | | | | | | |
|---|------|------|------|------|------|------|
| Above | - | 6 | 30 | 120 | 400 | 1000 |
| Up to | 6 | 30 | 120 | 400 | 1000 | 2500 |
| Tol. | ±0.1 | ±0.2 | ±0.3 | ±0.5 | ±0.8 | ±1.2 |

© Ø 0.1 A


Angles ± 2° Drilled holes +0.25 -0
All sharp edges removed R0.2 +0.2
Inside and Outside deburred
Surface roughness max. Ra 3.2

Stroke
Tol. +1.8
-1.6

| | | | | |
|-------------|--|-----------|----------|----------|
| | Drawn | | Pressure | 250 bar |
| | Cust. Ref. | | Weight | 21.83 kg |
| Item | CFGY0079643 | Reference | 7441650 | |
| Description | C2S.70.40.660 Fond/Circulaire-Douille/50 | | | |
| Finish | Primer | | | |



CFGCY0079643 - C2S.70.40.660 Fond/Circulaire~Douille/50



| PARTNO | POS. | DESCRIPTION | QTY. |
|--------------|------|---|------|
| MDL-090348 | 1 | Tube - Cylinder tube 80 x 70 ST52-H10 CB 80-5H10 L=0.855 | 1 |
| LSN06E | 2 | Welding-stud 3/8" BSP | 2 |
| MDL-011640 | 3 | Machined Endcap/Circular with Hole 28mm - Bore 70 | 1 |
| MDL-090346 | 4 | Rod - Hard Chrome Shaft 40 - HAC40 L=0.898 | 1 |
| | 5 | Bush 50 x 28 L=70 | 1 |
| DS2907013040 | 6 | Cylinder-head C2 - Bore 70 - Rod 40 - 250 bar | 1 |
| DS2907004 | 7 | Cylinder-piston C2 - Bore 70 | 1 |
| DS2906015 | 8 | Swage ring C25 Bore 60/63/70 | 1 |
| MDL-014997 | 9 | Spacer - Cylinder tube 55 x 40 ST52-H8 CB5575H8 L=0.092 mtr | 1 |
| SP06M | 10 | Dust plug outer thread 3/8" BSP | 2 |
| GN61180 | 11 | Grease nipple M6 - 180° | 2 |