

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

© $\varnothing 0.1$ A


Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$
All sharp edges removed R0.2 $+0.2$
Inside and Outside deburred
Surface roughness max. Ra 3.2

Stroke
Tol. $+1.8$
 -1.6

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	2.29 kg
Item	CFGY0079622	Reference	0415377	
Description	C2S.25.16.250 GK15DO~GK15DO			
Finish	Primer			



CFGCY0079622 - C2S.25.16.250 GK15DO~GK15DO



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 35 x 25 ST52-H10 CB 35-5H10 L=0.325	1
LSN04E	2	Welding-stud 1/4" BSP	2
DC3902501	3	Endcap C2/C3/P2 - Bore 25	1
GK15DO	4	Spherical-bearing GK 15 DO	2
MDL-090346	5	Rod - Hard Chrome Shaft 16 - HAC16 L=0.347	1
DS2902513016	6	Cylinder-head C2 - Bore 25 - Rod 16 - 250 bar	1
ASU1624653	7	Scraper 16 x 24.6 x 5.3	1
SA16225UN	8	Rod-seal 16 x 22 x 5 UN	1
BU2064262	9	Backup-ring 20.64 x 2.62 x 1.4	1
OR2063262	10	O-ring 20.63 x 2.62	1
OR2347262	11	O-ring 23.47 x 2.62	1
DS2902504	12	Cylinder-piston C2 - Bore 25	1
ZA2515125DBM	13	Piston-seal 25 x15 x 12.5 DBM	1
MDL-020787	14		1
SLBMM1015	15	Seallock-nut M10x1.5 Ø25mm	1
SP04M	16	Dust plug outer thread 1/4" BSP	2