



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{Ø } 0.1 \text{ A}$	Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed $R0.2 +0.2$ Inside and Outside deburred Surface roughness max. $Ra 3.2$	Stroke
Up to	6	30	120	400	1000	2500			Tol. $+1.8$
Tol.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2			-1.6

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	91.82 kg
Item	CFGCY0079550	Reference	0609000	
Description	C2S.70.50.3333 Capflange~G22,6KF			
Finish	Primer			



CFGCY0079550 - C2S.70.50.3333 Capflange~G22,6KF



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 80 x 70 ST52-H10 CB 80-5H10 L=3.436	1
ASV8L	2	Weld-on coupling ASV 8L	1
LSN06E	3	Welding-stud 3/8" BSP	1
MDL-010699	4	CapFlange Bore 70	1
MDL-090346	5	Rod - Nickle Chrome Shaft 50 - NIC50 L=3.459	1
KF22675D	6	G 22,6 KF L=75 ±1.5mm	1
DS2907013050	7	Cylinder-head C2 - Bore 70 - Rod 50 - 250 bar	1
ASU5060653	8	Scraper 50 x 60.6 x 5.3	1
SA506010UN	9	Rod-seal 50 x 60 x 10 UN	1
BU5969534	10	Backup-ring 59.69 x 5.34 x 1.52	1
DS2907004	11	Cylinder-piston C2 - Bore 70	1
DS2906015	12	Swage ring C25 Bore 60/63/70	1
VS8LS	13	End plug 8LS	1
MV8L	14	Swivel nut 8L MV8L	1
SP06M	15	Dust plug outer thread 3/8" BSP	1