

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

©	ϕ 0.1	A
---	------------	---



Angles ± 2° Drilled holes +0.25 -0
 All sharp edges removed R0.2 +0.2
 Inside and Outside deburred
 Surface roughness max. Ra 3.2

Stroke	Tol. +1.8 -1.6
--------	-------------------

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	45.12 kg
Item	CFGCY0079597	Reference	0326662	
Description	C2P.70.40.1500 Voeten-Bus/50			
Finish	Primer & RAL9005 Jet-black High-Gloss			



CFGCY0079597 - C2P.70.40.1500 Voeten~Bus/50



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 85 x 70 ST52-H8 CB 85-7.5H8 L=1.586	1
LSN06E	2	Welding-stud 3/8" BSP	2
MDL-011607	3	Side-lug	2
DS3907001A	4	Reinforced Endcap C2/C3 - Bore 70	1
MDL-090346	5	Rod - Nickle Chrome Shaft 40 - NIC40 L=1.609	1
	6	Bush 50 x 25 L=116	1
DS2907013040	7	Cylinder-head C2 - Bore 70 - Rod 40 - 250 bar	1
DS2907004S	8	Cylinder-piston C2P - Bore 70	1
ZAS705942T764	9	Piston stepseal 70 x 59 x 4.2	1
OR250726290P001	10	O-ring 25.07 x 2.62 - 90'-shore	1
GRE706597	11	Wear-ring 70 x 65 x 9.7	1
91666B	12	Grub screw M6x6 45H DIN 916	1
SP06M	13	Dust plug outer thread 3/8" BSP	2