



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{Ⓢ} \text{ } \varnothing \text{ } 0.1 \text{ } \text{A}$	Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed $R0.2 +0.2$ Inside and Outside deburred Surface roughness max. $Ra \text{ } 3.2$	Stroke Tol. $+1.8$ -1.6
Up to	6	30	120	400	1000	2500			
Tol.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2			

	Drawn		Pressure	320 bar
	Cust. Ref.		Weight	100.62 kg
Item	CFGY0079609	Reference	0334006	
Description	C3S.100.60.1500 GK60DO~GK60DO			
Finish	Primer			



CFGCY0079609 - C3S.100.60.1500 GK60DO~GK60DO



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 120 x 100 ST52-H8 CB 120-10H8 L=1.643	1
LSN12MM90	2	Welding stud 12mm 90 degrees	2
DC3910001	3	Endcap C2/C3 - Bore 100	1
GK60DO	4	Spherical-bearing GK 60 DO	2
MDL-033544	5	Pipe connection Ø12 x 1,5 to Valve Endcap-side - WLHL1215 L=0.732 mtr	1
MDL-033545	6	Pipe connection Ø12 x 1,5 to Valve Rod-side - WLHL1215 L=0.732 mtr	1
1003511090	7	Base plate 1003511090	1
FPO50D382F35	8	Counter balance Dual 3/8" Gasket mounted	1
912840109	9	Hex sock hd Cyl. bolt M8x40 DIN 912 / ISO 4762 Zinc-plated	4
VSR06WD	10	End Plug (CS) R3/8 VS-R06-WD	2
MDL-090346	11	Rod - Hard Chrome Shaft 60 - HAC60 L=1.669	1
DS3910013060	12	Cylinder-head C3 - Bore 100 - Rod 60 - 320 bar	1
ASU6070653T38	13	Scraper 60 x 70.6 x 5.3 - T38	1
SA607010UN	14	Rod-seal 60 x 70 x 10 UN	1
SAS6075163	15	Rod-seal 60 x 75.1 x 6.3	1
GRI606597	16	Guide-ring 60 x 65 x 9.7	2
BU8969534	17	Backup-ring 89.69 x 5.34 x 1.52	1
OR8969533P001	18	O-ring 89.69 x 5.33	1
OR9493262	19	O-ring 94.93 x 2.62	1
DS3910004	20	Cylinder-piston C3 - Bore 100	1
ZAS10084563	21	Piston-stepseal 100 x 84.5 x 6.3	1
GRE1009515	22	Wear-ring 100 x 95 x 15	2
OR408735390P001	23	O-ring 40.87 x 3.53 - 90'-shore	1
916816	24	Grub screw M8x16 45 H zinc-pl.	1