

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2



©	∅ 0.1	A
---	-------	---

Angles ± 2°  
 Drilled holes +0.25 -0  
 All sharp edges removed R0.2 +0.2  
 Inside and Outside deburred  
 Surface roughness max. Ra 3.2

Stroke	Tol. +1.8 -1.6
--------	-------------------

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	37.38 kg
Item	CFGY0079635	Reference	0326662	
Description	C2S.70.40.1500 Voeten-Bus/50			
Finish	Primer & RAL9005 Jet-black High-Gloss			

CFGCY0079635 - C2S.70.40.1500 Voeten~Bus/50



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 80 x 70 ST52-H10 CB 80-5H10 L=1.603	1
LSN06E	2	Welding-stud 3/8" BSP	2
MDL-011607	3	Side-lug	2
DS3907001A	4	Reinforced Endcap C2/C3 - Bore 70	1
MDL-090346	5	Rod - Nickle Chrome Shaft 40 - NIC40 L=1.626	1
	6	Bush 50 x 25 L=116	1
DS2907013040	7	Cylinder-head C2 - Bore 70 - Rod 40 - 250 bar	1
DS2907004	8	Cylinder-piston C2 - Bore 70	1
DS2906015	9	Swage ring C25 Bore 60/63/70	1
SP06M	10	Dust plug outer thread 3/8" BSP	2