


| All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask | | | | | | |
|---|------|------|------|------|------|------|
| Above | - | 6 | 30 | 120 | 400 | 1000 |
| Up to | 6 | 30 | 120 | 400 | 1000 | 2500 |
| Tol. | ±0.1 | ±0.2 | ±0.3 | ±0.5 | ±0.8 | ±1.2 |

| | | |
|-----------------------|---|-----------------------------|
| © \varnothing 0.1 A | Angles ± 2° Drilled holes +0.25 -0 All sharp edges removed R0.2 +0.2 Inside and Outside deburred Surface roughness max. Ra 3.2 | Stroke Tol. +1.8 -1.6 |
|-----------------------|---|-----------------------------|

| | | | |
|-------------|--------------------------------|---------------------------------|---------|
| | Drawn | Pressure | 250 bar |
| | Cust. Ref. | Cilinder achterbeugel dynamisch | Weight |
| Item | CFGY0072592 | Reference | 0354933 |
| Description | C2S.25.16.200 Bodem/Gat-Bus/30 | | |
| Finish | Primer | | |



CFGCY0072592 - C2S.25.16.200 Bodem/Gat~Bus/30



| PARTNO | POS. | DESCRIPTION | QTY. |
|--------------|------|--|------|
| MDL-090348 | 1 | Tube - Cylinder tube 35 x 25 ST52-H10 CB 35-5H10 L=0.276 | 1 |
| LSN04E | 2 | Welding-stud 1/4" BSP | 2 |
| MDL-011633 | 3 | Machined Endcap/Circular with Hole 12.2mm - Bore 25 | 1 |
| MDL-090346 | 4 | Rod - Hard Chrome Shaft 16 - HAC16 L=0.628 | 1 |
| | 5 | Bush 30 x 12 L=35 | 1 |
| DS2902513016 | 6 | Cylinder-head C2 - Bore 25 - Rod 16 - 250 bar | 1 |
| ASU1624653 | 7 | Scraper 16 x 24.6 x 5.3 | 1 |
| SA16225UN | 8 | Rod-seal 16 x 22 x 5 UN | 1 |
| BU2064262 | 9 | Backup-ring 20.64 x 2.62 x 1.4 | 1 |
| OR2063262 | 10 | O-ring 20.63 x 2.62 | 1 |
| OR2347262 | 11 | O-ring 23.47 x 2.62 | 1 |
| DS2902504 | 12 | Cylinder-piston C2 - Bore 25 | 1 |
| ZA2515125DBM | 13 | Piston-seal 25 x15 x 12.5 DBM | 1 |
| MDL-020787 | 14 | | 1 |
| SLBMM1015 | 15 | Seallock-nut M10x1.5 Ø25mm | 1 |
| SP04M | 16 | Dust plug outer thread 1/4" BSP | 2 |