



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask

Above	-	6	30	120	400	1000	All diameters $\text{⌀ } 0.1   A$	Angles $\pm 2^\circ$ Drilled holes $+0.25 -0$ All sharp edges removed $R0.2 +0.2$ Inside and Outside deburred Surface roughness max. $Ra 3.2$	Stroke Tol. $+1.8$ $-1.6$
Up to	6	30	120	400	1000	2500			
Tol.	$\pm 0.1$	$\pm 0.2$	$\pm 0.3$	$\pm 0.5$	$\pm 0.8$	$\pm 1.2$			

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	5.48 kg
Item	CFGCY0079564	Reference	0140034	
Description	C2S.40.28.315 Gabelkopf/50x35x16-Gabelkopf/50x35x16 (Schweißen)			
Finish	Primer			



CFGCY0079564 - C2S.40.28.315 Gabelkopf/50x35x16~Gabelkopf/50x35x16 (Schweißen)



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 50 x 40 ST52-H10 CB 50-5H10 L=0.400	1
LSN06E	2	Welding-stud 3/8" BSP	2
DC3904001	3	Endcap C2/C3/P2 - Bore 40	1
FS1710	4	Clevis 50x35x16 hole 16	2
MDL-090346	5	Rod - Hard Chrome Shaft 28 - HAC28 L=0.422	1
DS2904013028	6	Cylinder-head C2 - Bore 40 - Rod 28 - 250 bar	1
ASU2836653	7	Scraper 28 x 36.6 x 5.3	1
SA283873UN	8	Rod-seal 28 x 38 x 7.3 UN	1
BU3452353	9	Backup-ring 34.52 x 3.53 x 1.02	1
OR3452353	10	O-ring 34.52 x 3.53	1
OR3934262	11	O-ring 39.34 x 2.62	1
DS2904004	12	Cylinder-piston C2 - Bore 40	1
ZA4024184DBM	13	Piston-seal 40 x 24 x 18.4/6.3	1
OR171326290	14	O-ring 17.13 x 2.62 - 90'-shore	1
DS2904015	15	Swage ring C25 Bore 40	1
SP06M	16	Dust plug outer thread 3/8" BSP	2