



All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

©	Ø 0.1	A
---	-------	---

Angles ± 2°
 Drilled holes +0.25 -0
 All sharp edges removed R0.2 +0.2
 Inside and Outside deburred
 Surface roughness max. Ra 3.2

Stroke	Tol. +1.8 -1.6
--------	-------------------

	Drawn		Pressure	250 bar
	Cust. Ref.	Test grondschiif samenstellen	Weight	26.87 kg
Item	CFGY0078898	Reference	0332123	
Description	C2S.100.50.300 GEEN~GF40HO2RS			
Finish	Primer			



CFGCY0078898 - C2S.100.50.300 GEEN~GF40HO2RS



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 115 x 100 ST52-H10 CB11575H10 L=0.436	1
LSN08E	2	Welding-stud 1/2" BSP	2
DS3910001A	3	Reinforced Endcap C2/C3 - Bore 100	1
MDL-090346	4	Rod - Hard Chrome Shaft 50 - HAC50 L=0.462	1
GF40HO2RS	5	Housing for GF-40	1
GE40HO2RS	6	Spherical-plain-bearing GE 40 HO 2RS	1
DS2910013050	7	Cylinder-head C2 - Bore 100 - Rod 50 - 250 bar	1
ASU5060653	8	Scraper 50 x 60.6 x 5.3	1
SA506010UN	9	Rod-seal 50 x 60 x 10 UN	1
BU8969534	10	Backup-ring 89.69 x 5.34 x 1.52	1
OR8969533P001	11	O-ring 89.69 x 5.33	1
OR9493262	12	O-ring 94.93 x 2.62	1
DS2910004	13	Cylinder-piston C2 - Bore 100	1
ZA10075224DBM	14	Piston-seal 100 x 75 x 22.4/6.	1
OR346026290P001	15	O-ring 34.60 x 2.62 - 90'-shore	1
DS2909015	16	Swage ring C25 Bore 90/100	1
SP08M	17	Dust plug outer thread 1/2" BSP	2