

All tolerances according to KRAMP-norm • Unless stated otherwise • If in doubt please ask						
Above	-	6	30	120	400	1000
Up to	6	30	120	400	1000	2500
Tol.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

©	∅ 0.1	A
---	-------	---



Angles ± 2° Drilled holes +0.25 -0  
 All sharp edges removed R0.2 +0.2  
 Inside and Outside deburred  
 Surface roughness max. Ra 3.2

Stroke	Tol. +1.8 -1.6
--------	-------------------

	Drawn		Pressure	250 bar
	Cust. Ref.		Weight	37.22 kg
Item	CFGY0076715	Reference	0500766	
Description	C2S.80.50.700 GK50DO~GK50DO			
Finish	Primer			



CFGCY0076715 - C2S.80.50.700 GK50DO~GK50DO



PARTNO	POS.	DESCRIPTION	QTY.
MDL-090348	1	Tube - Cylinder tube 92 x 80 ST52-H10 CB 92-6H10 L=0.909	1
LSN08E	2	Welding-stud 1/2" BSP	2
DS3908001A	3	Reinforced Endcap C2/C3 - Bore 80	1
GK50DO	4	Spherical-bearing GK 50 DO	2
MDL-090346	5	Rod - Hard Chrome Shaft 50 - HAC50 L=0.954	1
DS2908013050	6	Cylinder-head C2 - Bore 80 - Rod 50 - 250 bar	1
ASU5060653	7	Scraper 50 x 60.6 x 5.3	1
SA506010UN	8	Rod-seal 50 x 60 x 10 UN	1
BU6922534	9	Backup-ring 69.22 x 5.34 x 1.52	1
OR6922533P001	10	O-ring 69.22 x 5.33	1
OR8060262P001	11	O-ring 80.60 x 2.62	1
DS2908004	12	Cylinder-piston C2 - Bore 80	1
ZA8060224DBM	13	Piston-seal 80 x 60 x 22.4/6.3	1
OR314226290P001	14	O-ring 31.42 x 2.62 - 90'-shore	1
DS2908015	15	Swage ring C25 Bore 80	1
MDL-014997	16	Spacer - Cylinder tube 65 x 50 ST52-H8 CB6575H8 L=0.090 mtr	1
SP08M	17	Dust plug outer thread 1/2" BSP	2